


# V形骨架端面油封



代号	名称	截面图	材料	压力	温度	圆周速度	特点							
RB	V形骨架端面油封		骨架+NBR	0	-30至100	≤12	固定在旋转体上密封端面装配紧固							
d	D	H	d	D	H	d	D	H	d	D	H	d	D	H
10	24	3.5	25	40	4	45	63	6.5	65	85	5.5	90	110	5.5
12	26	3.5	25	42	6	48	65	4.5	65	87	7.5	90	112	7.5
15	30	4	26	40	4	50	70	5.5	68	88	5.5	95	115	5.5
15	32	6	28	43	4	50	72	7.5	70	90	5.5	95	117	7.5
16	32	4	30	47	4.5	52	72	5.5	70	92	7.5	100	120	5.5
17	32	4	30	48	6.5	53	73	5.5	72	92	5.5	100	122	7.5
17	34	6	32	49	4.5	55	75	5.5	75	95	5.5	105	125	5.5
18	33	4	35	52	4.5	55	77	7.5	78	98	5.5	125	148	6.5
20	35	4	35	53	6.5	58	78	5.5	80	100	5.5	135	159	6.5
20	37	6	40	57	4.5	60	80	5.5	80	102	7.5			
22	40	4	40	58	6.5	60	82	7.5	85	105	5.5			
24	40	4	45	62	4.5	62	82	5.5	85	107	7.5			