



代号	名称	截面图	材料	压力	温度	圆周速度	特点
PF	纯四氟油封		橡胶+四氟+弹簧	≤1	FKM -20至200	≤1.5	具有较强的静密封性，抗磨性，耐高温，耐腐蚀，适应润滑不良工况

d	D	L	d	D	L	d	D	L	d	D	L	d	D	L
5	15	6	24	35	8	48	72	12	80	100	10	135	170	15
6	16	7	25	35	7	50	62	8	80	110	10	140	165	10
7	16	7	25	35	9	50	65	8	82	105	14	140	170	15
8	18	5	25	38	7	50	68	8	84	110	12	150	180	12
9.7	22	7	25	40	7	50	70	8	85	100	12	150	180	14
10	19	7	25	42	7	50	72	8	85	110	10	150	180	15
10	20	8	25	47	7	50	75	10	85	120	12	155	190	15
10	22	7	25	52	7	50	78	12	86	105	10	156	190	15
10	24	7	27	47	7	50	80	7	90	110	6	160	190	15
10	25	7	28	47	7	52	72	8	90	110	12	170	200	15
10	28	7	30	42	7	55	70	8	90	115	13	175	205	15
12	22	7	32	52	8	55	72	8	90	120	12	180	210	15
12	26	7	32	54	8	55	80	8	95	120	12	200	230	15
12	30	7	33	45	7	55	90	7	95	125	12	220	250	10
13	25	6	34	44	7	58	78	12	100	120	12	220	250	15
14	24	8	35	50	7	58	80	8	100	120	13	250	280	16
15	24	7	35	52	7	60	72	8	100	125	12	250	280	18
15	26	7	35	62	8	60	75	7	100	130	12	260	300	20
15	30	7	35	72	8	60	80	7	100	130	13			
15	35	10	37	50	10	60	80	10	105	130	8			
16	26	7	38	55	8	60	82	12	105	130	12			
16	30	10	38	58	8	60	85	8	110	128	9			
17	28	6	38	62	8	60	106	7	110	130	8			
17	30	7	40	52	8	62	80	8	110	130	12			
17	35	8	40	55	7	63	90	10	110	140	12			
18	28	7	40	60	8	65	80	10	110	140	13			
18	32	7	40	62	8	65	85	8	115	140	12			
18	35	7	40	67	7	65	90	10	115	150	12			
19	32	7	42	55	7	65	100	10	120	140	12			
20	30	7	42	60	8	70	85	8	120	140	13			
20	32	6	43	60	10	70	90	7	120	150	12			
20	35	7	45	58	7	70	90	10	125	150	12			
20	40	7	45	62	7	70	95	10	125	150	15			
20	47	7	45	65	8	70	100	10	125	160	12			
21	32	5	45	72	8	72	100	10	130	150	15			
22	40	7	47	65	10	75	95	10	130	160	12			
23	35	6	48	62	8	75	100	10	130	160	15			

其他截面

